



dLAN 200 AV_{desk}

Technical data

Standards	- Ethernet specifications IEEE 802.3, IEEE 802.3x, IEEE 802.3u, Auto MDI / X - HomePlug AV
Protocols	TDMA, CSMA/CA
Transmission speed	200 Mbps
Transmission method	asynchronous
Modulation	OFDM - 1155 carriers, 1024/256/64-QAM, QPSK, BPSK
Data path	Ethernet <-> power supply grid
Range	200m over household power supply grid
Security	128-bit AES encryption over household power supply grid
LEDs	- Power - dLAN (Link/Act) - Ethernet (100/Act) - Ethernet (10/Act) - Ethernet Collision
dLAN port	Euro mains plug
Device port	Ethernet RJ45
Power consumption	5.5 W (max.)
Power supply	AC 100-240V 50/60Hz
Temperature	Storage: -25°C – 70°C Operation: 0°C – 40°C
Ambient conditions	10–90% humidity (non-condensing)
System requirements	Ethernet port
Operating systems	Windows® 98, Windows® ME, Windows® 2000, Windows® XP, Linux®, Mac OS® X and all operating systems with TCP/IP support
Certifications	CE-compliant in accordance with the technical requirements of all EU countries and Switzerland: EN 55022 EN 50412 EN 60950

Sales information

Article number	01181 (DE/AT/CH/BE/IT), 01173 (NL/ESP), 01182 (UK), 01183 (FR)
EAN-Code	4250059611818 (DE/AT/CH/BE/IT), 4250059611733 (NL/ESP), 4250059611825 (UK), 4250059611832 (FR)
Warranty	3 years
Service & Support	Telephone and e-mail support for Austria, Belgium, France, Germany, Italy, the Netherlands, Spain, Switzerland and the United Kingdom. Please see the included support flyer or the devolo website for telephone numbers and e-mail addresses.
Design	Plastic desktop housing
Dimensions	153 x 105 x 35 mm (height x width x depth)
Weight	615 g
Package dimensions	188 x 302 x 115 mm (height x width x depth)
Accessories	- Ethernet cable RJ45-RJ45 (Cat 5) - Power cable - Documentation: printed installation guide - CD-ROM: PDF manual, configuration software for Windows® 98, Windows® ME, Windows® 2000, Windows® XP, Linux®, Mac OS® X, Additional software: devolo Informer, devolo Easyshare, devolo Easyclean